


SOLAR'S MOST TRUSTED



# REC ALPHA<sup>®</sup> PURE-RX SERIES

DATASHEET



9 A MODULE CURRENT  
COMPATIBLE WITH MLPE

450 - 470W  
HETEROJUNCTION  
TECHNOLOGY

22.6% EFFICIENCY  
>92% POWER IN YEAR 25  
-0.24%/K TEMPERATURE  
COEFFICIENT OF  $P_{MAX}$




ELIGIBLE

# REC ALPHA® PURE-RX SERIES DATASHEET

Measurements in [inches] and mm

GENERAL DATA	
Cell Type	88 half-cut bifacial REC heterojunction cells, with gapless technology
Glass	0.13 in solar glass with anti-reflective surface treatment in accordance with EN12150
Backsheet	Highly resistant polymer (Black)
Frame	Anodized aluminum (Black)
Junction Box	4-part, 4 bypass diodes, IP68 rated, in accordance with IEC 62790:2020
Connectors	Stäubli MC4 PV-KBT4/KST4 (12 AWG) in accordance with IEC 62852:2014, IP68 only when connected
Cable	12 AWG solar cable, 66.9 in (1.70 m) + 66.9 in (1.70 m) in accordance with EN50618:2014
Dimensions	68.0 x 47.4 x 1.2 in (22.4 ft²) / 1728 x 1205 x 30 mm (2.08 m²)
Weight	50.0 lb / 22.7 kg
Origin	Made in Singapore



Specifications subject to change without notice.

ELECTRICAL DATA		PRODUCT CODE*: RECXXXAA PURE-RX		
Power Output - P <sub>MAX</sub> (WP)	450	460	470	
Watt Class Sorting - (W)	0/+10	0/+10	0/+10	
Nominal Power Voltage - V <sub>MPP</sub> (V)	54.3	54.9	55.4	
Nominal Power Current - I <sub>MPP</sub> (A)	8.29	8.38	8.49	
Open Circuit Voltage - V <sub>OC</sub> (V)	65.6	65.8	65.9	
Short Circuit Current - I <sub>SC</sub> (A)	8.81	8.88	8.95	
Power Density (W/ft²)	20.1	20.5	21.0	
Panel Efficiency (%)	21.6	22.1	22.6	

CERTIFICATIONS	
ISO 14001; ISO 9001; IEC 45001; IEC 62941	
IEC 61215:2021; IEC 61730:2023; UL 61730	
ISO 11925-2	Ignitability (EN 13501-1 Class E)
IEC 62716	Ammonia Resistance
IEC 61701	Salt Mist (SM6)
IEC 61215:2016	Hailstone (35mm)
UL 61730	Fire Type 2



NOMOT		PRODUCT CODE*: RECXXXAA PURE-RX		
Power Output - P <sub>MAX</sub> (W <sub>p</sub> )	343	350	358	
Nominal Power Voltage - V <sub>MPP</sub> (V)	51.2	51.7	52.2	
Nominal Power Current - I <sub>MPP</sub> (A)	6.70	6.77	6.86	
Open Circuit Voltage - V <sub>OC</sub> (V)	61.8	62.0	62.1	

Values at standard test conditions (STC: air mass AM 1.5, irradiance 1000 W/m², temperature 25°C), based on a production spread with a tolerance of P<sub>MAX</sub>, V<sub>OC</sub> & I<sub>SC</sub> ±3% within one watt class. Nominal module operating temperature (NMOT: air mass AM 1.5, irradiance 800 W/m², temperature 20°C, windspeed 1 m/s). \*Where xxx indicates the nominal power class (P<sub>MAX</sub>) at STC above.

MODULE RATINGS	
Module Operating Temperature [T <sub>98</sub> ]	158°F (70°C)
Min. Environmental Temperature	-40°F (-40°C)
System Voltage	1000 V
Maximum Test Load (4 Point Mounting, Front)*	+7000 Pa (1.02 lbs/in²)
Maximum Test Load (4 Point Mounting, Rear)*	-4000 Pa (0.58 lbs/in²)
Maximum Test Load (6 Point Mounting, Front)**	+8000 Pa (1.16 lbs/in²)
Maximum Test Load (6 Point Mounting, Rear)**	-6000 Pa (0.87 lbs/in²)
Max Series Fuse Rating	25 A
Max Reverse Current	25 A

Design load = Test load / 1.5 (safety factor)  
 \* 98th percentile operating temperature  
 \*\* IEC 61730/UL 61730 certified. Refer to installation manual.  
 \*\*\* Internal testing. Refer to installation manual.

TEMPERATURE RATINGS*	
Nominal Module Operating Temperature	44 ± 2°C
Temperature coefficient of P <sub>MAX</sub>	-0.24%/K
Temperature coefficient of V <sub>OC</sub>	-0.24%/K
Temperature coefficient of I <sub>SC</sub>	0.04%/K

\*The temperature coefficients stated are linear values


DELIVERY INFORMATION	
Panels per Pallet	33
Panels per 40 ft GP/high cube container	594 (18 Pallets)
Panels per 53 ft truck	792 (24 Pallets)

	Standard		REC ProTrust	
	No	Yes	Yes	Yes
Installed by an REC	No	Yes	Yes	Yes
Certified Professional				
System Size	All	<25 kW	25-500 kW	
Product Warranty (yrs)	20	25	25	
Power Warranty (yrs)	25	25	25	
Labor Warranty (yrs)	0	25	10	
Power in Year 1	98%	98%	98%	
Annual Degradation	0.25%	0.25%	0.25%	
Power in Year 25	92%	92%	92%	


REC ProTrust Warranty applies only for i) REC panels installed by an REC Certified Solar Professional, and ii) panels have been registered by the installer with REC. Subject to System Size and further conditions. See [www.recgroup.com](http://www.recgroup.com) for details.

### LOW LIGHT BEHAVIOR

Typical low irradiance performance of module at STC:



Available from:



Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

REC Solar PTE. LTD.  
 20 Tuas South Ave. 14  
 Singapore 637312  
 post@recgroup.com  
 www.recgroup.com



REF: PM-DS-12-06-REV-4.3/B UL EN12.2024